



## 油拖网

对于高粘度的原油，常温下凝结成块状固体，漂浮在水面或悬浮在水中，机械收油设备难以回收，使用油拖网可得到较好的回收效果。油拖网主要由框架、浮体、主体网、拖网、尼龙布袋组成。拖网与主体网可分离，收满时可更换拖网。



### OIL TRAWL

As for crude oils of high viscosity, which are condensed into solid blocks at room temperature, floating or shifting in waters, and are difficult to be retrieved by a mechanical recovery device. A better recovery can be made with the oil trawl. The oil trawl is mainly composed of a frame, buoy, main net, dragnet and nylon fabric bag. The dragnet is detachable from the main net. When the net is full, it can be replaced with a new one.

### 技术参数 TECHNICAL PARAMETER

| 型号<br>Model<br>参数<br>Parameter | SW-2              | SW-3              | SW-4              | SW-5              | SW-10             |
|--------------------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| 框架尺寸(mm)<br>Frame Size         | 2150×650×<br>1080 | 2150×650×<br>1080 | 2150×650×<br>1080 | 2150×650<br>×1080 | 2150×650×<br>1080 |



|   |   |                   |                   |                   |                   |
|---|---|-------------------|-------------------|-------------------|-------------------|
| 袋网容量(m <sup>3</sup> )<br>Net Bag<br>Volume    | 2   | 3                 | 4                 | 5                 | 10                |
| 网眼尺寸<br>Mesh Size                             | 5×5 或 10×10<br>(5×5 or 10×10)   |                   |                   |                   |                   |
| 拖拽速度(Kn)<br>Towing Speed                      | 0.5~1   | 0.5~1             | 0.5~1             | 0.5~1             | 0.5~1             |
| 包装箱尺寸<br>(mm)<br>Package Box<br>Size          | 2280×1230<br>×870   | 2280×1230<br>×870 | 2280×1230×<br>870 | 2280×1230<br>×870 | 2280×1230×<br>870 |
| 悬臂<br>Boom Arm                                | 10.5m (可根据用户需求配置)<br>It can be configured according to the user's needs.  |                   |                   |                   |                   |
| 拖带用围油栏<br>Containment<br>Boom for<br>Trailing | 1000 型×10m, 2 条 (可根据用户需求配置)<br>Type 1000*10m, 2 pieces<br>(It can be configured according to the user's needs.) |                   |                   |                   |                   |

注：产品不断改进，若发生变化，恕不另行通知，以供需双方确认数据为准。

Note: The technical parameter is subject to change without notice due to modification to the product and shall be confirmed by the manufacture and the customer.