



PVC 轻便储油罐

该储油罐罐体由两面涂覆 PVC 树脂的涤纶帆布主体材料，热粘合而成。耐侯、耐油性能良好，耐酸碱性能好，强度高，使用寿命长。罐体上口设有多条双层 PVC 布热粘合的强力带，用专用紧固扣固定在专用支架上。专用支架为分体的多边形架体，分为上架、下架、立柱等，可现场快速组装，操作极为方便。

该储油罐，一般用于野外作业，适用于运输条件有限，而又要求迅速布置完善的场合，既可用于岸上，也可用于船上临时贮油之用。



LIGHTWEIGHT OIL STORAGE TANK

The tank's body is formed with the thermal-bonded polyester canvas coated with PVC resins on its sides. It is well resistant to weather, oil, acids and alkali. It has high strength and a long service life. The upper opening of the tank body is provided with multiple PVC double-layer thermally bonded power bands, which are fixed on the special bracket with special fastening buckle. The special support is divided into three parts, i.e. upper frame, lower frame, column, etc. It can be quickly assembled on site, and the operation is very convenient.

It generally used in field operations, and the storage tank is suitable for occasions where transportation conditions are limited and rapid arrangement is required. It can be used for temporary storage of oil on board ships as well as on shore.



技术参数:

型号 Model	QG-V2	QG-V3	QG-V5	QG-V8	QG-V10
项目 Parameter					
储油量 (m ³) Storage Volume	2m ³	3m ³	5m ³	8m ³	10m ³
外形尺寸 (mm) Dimensions	φ 1600×1280	φ 1900×1380	φ 2400×1380	φ 2700×1380	φ 3400×1380

注：产品不断改进，若发生变化，恕不另行通知，以供需双方确认数据为准。

Note: The technical parameter is subject to change without notice due to modification to the product and shall be confirmed by the manufacture and the customer.